

Bedienkräfte

für Jalousien- und Rollladengetriebe

	Maximales Abtriebsdreh- moment	Dabei entstehendes Antriebsdreh- moment	Ausladung			
			120 mm	140 mm	160 mm	180 mm
434F504 2:1 Kegelradgetriebe	3 Nm	2,5 Nm	21,0 N 2,1 kg	18,0 N 1,8 kg	16,0 N 1,6 kg	14,0 N 1,4 kg
444F001 2:1 Kegelradgetriebe	7 Nm	4,1 Nm	34,0 N 3,4 kg	30,0 N 3,0 kg	26,0 N 2,6 kg	23,0 N 2,3 kg
446F001 2,7:1 Kegelradgetriebe	9 Nm	4,0 Nm	34,0 N 3,4 kg	29,0 N 2,9 kg	25,0 N 2,5 kg	22,0 N 2,2 kg
447F001 3:1 Kegelradgetriebe	9 Nm	4,8 Nm	40,0 N 4,0 kg	34,0 N 3,4 kg	30,0 N 3,0 kg	27,0 N 2,7 kg
456F001 4:1 Kegelradgetriebe	12 Nm	3,7 Nm	31,0 N 3,1 kg	27,0 N 2,7 kg	24,0 N 2,4 kg	21,0 N 2,1 kg